

Specification Sheet – Eco & Quadra Sparkling Range



Instant filtered boiling, chilled & sparkling water.



The Billi Sparkling systems are the ultimate drinking water appliances which deliver boiling, chilled & professional sparkling filtered water instantly. They deliver the following benefits:

Professional saturated sparkling system

The CO₂ injection system used in the Billi Sparkling range ensures the saturation of CO₂ in the water is high which means it has a better life and, consequently, taste.

Adjustable chilled temperature

A simple adjustable control knob allows the chilled water temperature to be raised to 15°C or lowered to 6°C for perfectly chilled, refreshing drinks, with your required temperature being quickly reached and maintained.

Adjustable sparkling water

Adjust the level of sparkling to suit your taste. With adjustable controls up to 5 bar of CO₂ pressure, this offers the world's best carbonation system.

Safety first

Billi's SplashFree boiling water delivery electronically varies the water flow, slowing momentarily to eliminate splashing as the water first enters the cup. All Billi dispensers are supplied standard with a safety switch.

Cupboard fitment options

The Billi Sparkling range is supplied as two modules enabling multiple cupboard fitment options to maximise the use and efficiency of your cupboard space.

Better for general health

The sparkling system includes a silver ion (Ag⁺) system which benefits the health of the user and the unit and eliminates any potential for growth of harmful bacteria.



Specification Sheet – Eco & Quadra Sparkling Range

Specification and Guide to model selection

Product Number	Description	Initial cup delivery and suggested no. of persons	Chilled & sparkling cups / hour	Boiling cups / hour	Total current draw (amps)		Unit Height (mm)	Unit Width (mm)	Unit Depth (mm)
903000	Eco Sparkling	10	60	90	2 x 10	C&S	385	240	325
						Boiling	340	180	360
903060	Quadra Sparkling 460	60	120	180	2 x 10	C&S	385	240	325
						Boiling	340	180	460
903100	Quadra Sparkling 4100	100	120	250	1 x 10 1 x 15	C&S	385	240	325
						Boiling	340	180	460

Please note: The BCS Sparkling consists of two modules, the Chilled and Sparkling (C&S) module, and the Boiling module.

Water Supply

A single 15mm (1/2") stop-tap with a male thread should be installed in an easily accessible position. Water supply must be microbiologically safe to drink, with a minimum dynamic water pressure of 250kPa to a maximum of 1200kPa.

Electrical installation requirements

The Billi BCS Sparkling consists of two modules and both require their own standard 10 amp power outlet. It is supplied with a 1 metre flex cord and plug.

CO2 Gas Cylinder

The CO2 gas cylinder supplied must be secured in a suitable location. Each cylinder contains 600g of CO2 and should be installed in a well ventilated area. Each cylinder will provide between 200-350L of sparkling water depending on the unit settings. The MSDS is available on www.billi.com.au for a complete list of specifications and warnings. Replacements are available from Billi.

Warranty

The Sparkling range is covered by a comprehensive 2 year warranty on all parts and labour.

Technical Advice

Contact Billi Pty Ltd on 1800 812 321

Filtration

Billi have partnered with globally recognised brand Pentair Everpure to create the most technologically advanced filtration for instant boiling and chilled filtered water systems. It removes sediment and chemicals, allows the flow of minerals through without scale build up and suppresses harmful bacteria in the water. Due to the unique Fibredyne™ technology, our filters have a longer life, higher flow rate and lower pressure drop, leaving you with healthy fresh water. All Billi cartridges are certified by global public safety agency NSF International.

Filter changes are made simple by our swing-change system and replacement cartridges are available online at www.billi.com.au. Optional sub micron filters are available.

Options and accessories

Dispenser Styles: The Quadra Sparkling is supplied with a standard XL levered dispenser.

Dispenser Finishes: Standard finish for the Dispenser is Bright Chrome. Optional finish— Brushed Chrome, Gloss Black or Matte Black.

Billi Font: Allows the dispenser to be located away from sink areas.

Finished in polished Stainless Steel, optional Brushed Chrome, Gloss Black or Matte Black finish available.

Dispenser Riser: 70mm dispenser extension - supplied standard with the Billi Font.

Certifications

Every Billi drinking water appliance is manufactured under a certified quality control system. The Billi Quadra models have been tested and comply with all required standards including: Watermark Licence Number 21525; Tested to; AS3498 and AS/NZS4020; Victorian Electrical Safety Act 1998 Approval Number CS100600V, AS/NZS ISO 9002; AS1428 Accessibility Design Requirements; Section J6 of the BCA; Certificate Number QEC 11627; C-Tick approved.

Install Diagram

